

CATV Aerial Trunk Cable Type QR

CATV 3,1/13,0 - QR 540 JCAM 109

Nexans Ref.: 10021679

Country Ref.: 1092654

EAN 13: 7045210007428

CATV Aerial Trunk Cable with Welded Aluminium Tube and Flooding Compound

DESCRIPTION

This cable has been thoroughly tested in our markets and contains a flooding compound between the outer conductor (welded aluminium tube) and the outer sheath. This provides a water-tight barrier in the case of outer sheath damage.

The cable can also be delivered as an underground cable.

STANDARDS

International EN 50117

CHARACTERISTICS

Construction characteristics

Type of conductor	Circular, solid
Conductor material	Copper-clad aluminum
Insulation	Foamed PE
Material used for longitudinal water tightness	Flooding compound
Outer conductor	Welded aluminium
Suspension wire	Steel wire
Outer sheath	PE
Sheath colour	Black

Dimensional characteristics

Conductor diameter	3.2 mm
Diameter over insulation	13.03 mm
Diameter over external conductor / metallic screen	13.72 mm
Nominal outer diameter	15.49 mm
Height	20 mm
Diameter over suspension strand	4.6 mm
Approximate weight	196 kg/km

Usage characteristics

Length	1000 m
Packaging	Drum

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Nexans is indicative only and shall not be binding on Nexans or be treated as constituting a representation on the part of Nexans.

Generated 12/2/21 www.nexans.no Page 1 / 1

