

PFSK 16/2 0,5mm²

D2x0,5 PFSK 440V

Nexans Ref.: 10172154
Country Ref.: 1060477
EAN 13: 7045210056105

DESCRIPTION

Application

These flexible multicore cables are used for internal cabling and inter-connection of airborne and ground electronic equipment and instrumentation. Outdoor usage only when protected.

Description

- 16/0.2 mm tinned copper stranded conductors
- PVC insulation
- Conductors laid up in concentric layer
- Overall tinned copper braided screen
- Grey PVC outer sheath

50 core :

- Central core red, blue, white
- 1st layer red, blue, 7 white cores
- 2nd layer red, blue, 14 white cores
- 3rd layer red, blue, 20 white cores



DECLARATION OF PERFORMANCE

E_{ca}

STANDARDS

National DEF STAN 61-12 part 4



Conductor flexibility
Stranded



Rated Voltage U_{o/U}
(Um)
250/440 V



Mechanical
resistance to
impacts
**Normal domestic
use**



Operating temp.
-20 - 50 °C



Bending factor
when laying
6 (xD)



Operation bending
rad.
- mm



Minimum
installation
temperature
- °C



Water proof
Temporary

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Nexans is indicative only and shall not be binding on Nexans or be treated as constituting a representation on the part of Nexans.

Generated 5/20/22 www.nexans.no Page 1 / 2

PFSK 16/2 0,5mm²

D2x0,5 PFSK 440V

CHARACTERISTICS

Construction characteristics

Conductor material	Tinned copper
Conductor flexibility	Stranded
Core lay-up	In concentric layer
Insulation	PVC
Screen	Tinned copper braid
Outer sheath	PVC
Sheath colour	Grey
With Green/Yellow core	No

Dimensional characteristics

Number of cores	2
Nominal outer diameter	6.1 mm
Number of wires per strand	16
Conductor cross-section	0.5 mm ²
Wire diameter	0.2 mm
Approximate weight	48.5 kg/km
Conductor diameter	0.798 mm

Electrical characteristics

Max. DC resistance of the conductor at 20°C	40 Ohm/km
Maximum operating voltage	440 V
Capacity core to screen	200 pF/m
Rated Voltage U _o /U (U _m)	250/440 V

Mechanical characteristics

Mechanical resistance to impacts	Normal domestic use
----------------------------------	---------------------

Usage characteristics

Operating temperature, range	-20 - 50 °C
Bending factor when laying	6 (xD)
Laying operation bending radius	- mm
Minimum installation temperature	- °C
Water proof	Temporary
Chemical resistance	Atmospheric
Resistance to vibrations	Low