

N-LINE Tele/data Kategorikabel

N-LINE Kat6 U/UTP 4Par 16-100

Nexans Ref.: 10211559
Country Ref.: 1087703
EAN 13: 7045210057003

Datacable in tube

DESCRIPTION

Corrugated PP pipes prewired with datacable.



DECLARATION OF PERFORMANCE

Eca

STANDARDS

International EN 50173



Conductor flexibility
-



Rated Voltage Uo/U (Um)
-



Flame retardant
Yes



Max.conductor temp.in service
70 °C

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Nexans is indicative only and shall not be binding on Nexans or be treated as constituting a representation on the part of Nexans.

Generated 1/20/22 www.nexans.no Page 1 / 2

N-LINE Tele/data Kategorikabel

N-LINE Kat6 U/UTP 4Par 16-100

CHARACTERISTICS

Construction characteristics

Conductor flexibility	-
Conductor material	Annealed copper
Insulation	PVC
Outer sheath	PVC
Sheath colour	White
Type of conductor	Circular, solid

Dimensional characteristics

Approximate weight	30 kg/km
Conductor cross-section	- mm ²
Conductor diameter	0.5 mm
Nominal outer diameter	4.9 mm
Number of cores	8
Number of pairs	4
Tube diameter	16 mm

Electrical characteristics

Maximal operating frequency	250 MHz
Rated Voltage U _o /U (Um)	-

Usage characteristics

Category	Cat. 6
Flame retardant	Yes
Length	100 m
Max. conductor temperature in service	70 °C
Packaging	Box