

N-LINE Tele/data Kategorikabel

N-LINE Kat.6 1xF/UTP + 1xU/UTP 20-150

Nexans Ref.: 10537392

Country Ref.: 1087876

EAN 13: 7045210120912

N-LINE Kat.6 1xF/UTP + 1xU/UTP 20-150 Nettverkskabel

DESCRIPTION

Corrugated PP pipes prewired with datacable.



STANDARDS

International EN 50173



Conductor flexibility



Rated Voltage Uo/U (Um)



Flame retardant
Yes



Max.conductor temp.in service
70 °C

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Nexans is indicative only and shall not be binding on Nexans or be treated as constituting a representation on the part of Nexans.

Generated 1/20/22 www.nexans.no Page 1 / 2

Nexans

N-LINE Tele/data Kategorikabel

N-LINE Kat.6 1xF/UTP + 1xU/UTP 20-150

CHARACTERISTICS

Construction characteristics

Conductor flexibility	
Conductor material	Annealed copper
Insulation	PVC
Outer sheath	PVC
Sheath colour	White
Type of conductor	Circular, solid

Dimensional characteristics

Approximate weight	30 kg/km
Conductor cross-section	- mm ²
Conductor diameter	0.5 mm
Nominal outer diameter	4.9 mm
Number of cores	8
Number of pairs	4
Tube diameter	16 mm

Electrical characteristics

Maximal operating frequency	250 MHz
Rated Voltage U _o /U (Um)	

Usage characteristics

Category	Cat. 6
Flame retardant	Yes
Length	150 m
Max. conductor temperature in service	70 °C
Packaging	Barrel