

240 System(9.45 Inch)

FIBREROUTE 240mm(9.45 inch) Channel Cover

Nexans Ref.: N350.240FC10P

Nexans Fibre Trunking System provides a dedicated pathway for fibre optic cables and cords to protect them from accidental damage. The system offers a flexible, high-capacity solution for data centre containment which is easy to install and reconfigure to meet future needs.

DESCRIPTION

- Pathway system designed for accommodation of Data Center fibre cables
- Cover for 240mm(9.45 inch) width channel
- Tough, flame retardant PVC material

The Nexans Fibre Trunking System provides a dedicated pathway through data centre spaces and IT facilities for routing fibre cables.

The rigid channel with matching cover protects fibre optic cables from damage.

All components of the system are made of tough, fire retardant materials.

The system components have a smooth inner surface to ensure a safe path for fibre optic cables and feature internal radius management to facilitate the maintenance of bend radii for cables and patch cords.

The Cover for the 240mm(9.45 inch)Channel provides protection to fibre cables and cords from dust and falling items.

All components of the system including the covers can be installed and uninstalled without special tools.

Size:

Depth 12mm(0.47")

Length 2000mm(78.7")

Width 274mm(10.8")



STANDARDS

International EN 50173-5; ISO/IEC 24764

National UL 94 V0



Operating temp.
-25 - 60 °C



Storage temperature, range
-45 - 60 °C

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Nexans is indicative only and shall not be binding on Nexans or be treated as constituting a representation on the part of Nexans.

Generated 12/2/21 www.nexans.no Page 1 / 2

240 System(9.45 Inch)

FIBREROUTE 240mm(9.45 inch) Channel Cover

CHARACTERISTICS

Construction characteristics

Colour	Yellow
Material	PVC

Dimensional characteristics

Approximate net weight	- kg
Approximate weight	1 kg/m
Depth	12 mm
Length	2000 mm
Width	274 mm

Mechanical characteristics

Max. Load. Long Term	- N
----------------------	-----

Usage characteristics

Operating temperature, range	-25 - 60 °C
Storage temperature, range	-45 - 60 °C